



# Fotojet Pro Gloss

Super weight glossy photo base paper with a nanoporous coating which absorbs inks instantly into the surface and produces stunning photographic results. Papers can accept high levels of dye and pigmented ink which dry instantly, exhibiting superior flatness and colour brilliance. Ultra Pro paper is the ultimate for photographic images from your digital camera, photo CD, etc.

# **Printing Systems**



# **Formats**

| Art.Number      | Basic weight (g) | Format | Packing quantity |
|-----------------|------------------|--------|------------------|
| 23708.210.44100 | 210              | A4     | 50               |

# Technical data

### Characteristic



- Dye based inks will be immediately touch dry, pigmented inks may take a few minutes more depending on the ink density.
- Single, microporous coated photopaper
- True colour
- Suitable for Ink Jet printer
- · Excellent runnability
- · Good flatness
- Brilliant high resolution colour prints
- Instant dry
- · Splash resistant

# **Finish**

• White glossy



### **Specifications**

| Basic weight (g)  | 210         |
|-------------------|-------------|
| Basic weight (oz) | 7.41        |
| Coating Printside | For Ink Jet |
| Width (inch)      | 8.27        |
| Width (mm)        | 210         |
| Printside         | Glossy side |
| Format            | A4          |
| Length (inch)     | 11.69       |
| Length (mm)       | 297         |
| Base Material     | Paper       |
| Packing quantity  | 50          |

# Compatibility

• For use on most small format lnk Jet printers such as: HP, Canon, Epson, Apple, Digital, Kodak, Lexmark, Olivetti, Tektronix, Xerox, etc.

# Handling

- Please follow the handling instructions supplied with this product as well as the Ink Jet Printer manufacturers manual.
- Avoid moisture and fingerprints.

### **Storage**

- Once packaging is opened, store at a room temperature of 15 25°C and at a humidity of 30 60 %
- Store in a cool and dry place

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.







