

## DATA SHEET

## Tack P WO

Matt white opaque polypropylene multilayer adhering film for photographic posters, mock ups, signage, decals, point of sale displays, signs and labels. A soft backlayer clings without any adhesive to most clean smooth surfaces like glass, plexiglass, metal, wood etc. This film can be repositioned without leaving any adhesive residue.

## Printing Systems



## Formats

Art.Number	Nominal thickness (mm)	Format	Packing quantity
22TO0.160.44800	0.200	A4	500
22TO0.160.43100	0.200	A3	50
22TO0.160.41800	0.200	A3	500

## Technical data

**Characteristic**

- Back layer clings to smooth surfaces (glass, metal) without adhesives, easy to remove
- Brilliant Colour Vibrancy
- Suitable for Ink Jet printer
- Clings to smooth surfaces like glass, plexi etc.
- Can be repositioned without permanently bonding to surfaces
- Excellent outstanding durability of the prints when using pigmented inks
- Instant dry

**Finish**

- White, semi matt

## Compatibility

## Handling

- Between 15-30°C and 30-70% r.h.
- Printer Mode: photo quality, coated paper, o.e.
- Print side = matt white side
- A preconditioning period of 24 hours within the printing environment is recommended.
- Please follow the handling instructions supplied with this product as well as the Ink Jet Printer manufacturers manual.
- Avoid moisture and fingerprints.

## Storage

- Once packaging is opened, store at a room temperature of 15 - 25°C and at a humidity of 30 - 60 %
- Store in a cool and dry place

## Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.