

DATA SHEET 38SLZ.050.44000

## Signolit SLZ

Polyester film, matt translucent, stable to heat. For DTP applications suitable. The film can be copied directly onto offset and screen printing plates.

### Printing Systems



### Formats

Art.Number	Thickness	Format	Packing quantity
38SLZ.050.44000	0.095 mm	DIN A4	100 sheets
38SLZ.050.43000	0.095 mm	DIN A3	100 sheets

### Technical data

#### Characteristic



- Duplex printing possible
- Excellent dimensional stability
- Excellent runnability
- Heat resistant
- Tear resistant
- Splash resistant
- Resistant against chemicals in toner blackening devices
- Accepts writing with ball point pens, felt tip pens and pencils

## Finish

- Translucent matt

## Specifications

Width (mm)	210
Thickness	0.095 mm
Format	DIN A4
Length (mm)	297
Base Material	PET film
Packing quantity	100 sheets

## Compatibility

### Handling

#### **Special hints for reproductionable originals:**

Toner compressors do contain solvents due to which the toner particles swell. The thereby achieved density is sufficient for reproductionable originals. Precondition is that the toner blackening is set at a high level when printing SLZ. Grey haze on unprinted areas and „spiderweb“ effects around letters or areas are an indication that the toner density is too high.

Manufacturers of toner compressors recommend to print SLZ with printers made by Canon or HP.

Machines that are using the new polymer toners are not suitable for toner blackening.

### Storage

- Shelf life: 1 year after delivery
- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

#### **Product liability clause**

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.