

DATA SHEET 22PMR.060.09110

## Label Jet PP Matt White R

White matt self-adhesive PP film with paper backing, removable adhesive. Ideal for stickers, signs and decals.

### Printing Systems



### Rolls

Art.Number	Width (mm)	Thickness	Length (m)
22PMR.060.09110	1070	0.060 mm	bulk roll

### Technical data

#### Characteristic

- High brilliance of colours
- Good wet smear resistance
- High Level Ink Absorption
- Inkjet coating and adhesive for the indirect food contact ISEGA / FDA-certified
- Low-reflective printing surface
- Tear resistant
- Very fast ink drying
- Universal use
- Removable

#### Finish

- self-adhesive with paper backing
- White matt

## Specifications

Release liner	siliconized paper
Coating Printsides	microporous coating
Width (mm)	1070
Thickness of carrier material	0.060 mm
Adhesion strength	>/= 3.5 N, after 24 h >/= 5.0 N (AA02 based on FINAT FTM1)
Type of adhesive	acrylate dispersion, removable
Length (m)	bulk roll
Roll width / Roll usable width	Please contact Folex if you need other roll widths and roll lengths. We can convert the rolls according to your wishes.
Base Material	Polypropylene
Total thickness	0.170 mm

## Compatibility

### Handling

- Gluing:

All even, smooth surfaces which are dry and free of dirt, grease, silicon etc. can be adhered. The surface to be glued must be checked for suitability before adhesion and properly prepared (cleaned). It is up to the user to test for their own suitability/application, due to the wide variety of surfaces, applications & desired results.

Gluing temperature at least 5° C

Service temperature min -10°C, max +80°C

- Durability:

The durability of the glued label is heavily influenced by the prevailing ambient conditions, the place of use and the bases!

### Storage

- Shelf life: 1 year after delivery
- In its original packing at 20-25°C, 45-55% humidity.

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.